

BID LIST NO. 0380

SPECIFICATION FOR FILM, STRETCH WRAP

PROPERTY NUMBERS: 201561, 201626

General Requirements

The product shall maintain a stretch memory adequate to provide an unionization force during handling and shipment. It shall provide sufficient cling so that heat sealing or other fastening methods is not required for bonding film layers securely. The film shall be suitable for use on a Silver Spiral Wrapper from Radiant Engineering, Inc.

Specific Requirements

Width of Roll

Property No. 201561 20" \pm 0.5" (508 mm \pm 13 mm)
Property No. 201626 60" \pm 0.5" (1524 mm \pm 13 mm)
Length of Roll 5000 - 6000 ft. (1524 - 1829 m)
Thickness of Film 0008" \pm 0.00005" (0.020 \pm 0.001 mm)
Color Shall be uniformly transparent
Finish Smooth on both sides
Odor..... Free of objectionable odors

Sample Requirement

A one-roll sample of the 20" width is required for testing. Additional rolls may be purchased if necessary.

Packaging

The product shall be single wound on a roll having a core capable of supporting the roll without collapsing or interfering with the easy unrolling of the film.

Qualified Products List

The following products have been tested and comply with the current specifications.

1. Presto Products, Inc. Powergard
2. Borden Chemical Corp. Loadmaster S
3. Englewood Co., Inc. Super Stretch III No. 84-14
4. Ohio Poly Corporation Elastifilm and Phase I
5. Mobil Wrap X-80
6. Co-Ex Plastics, Inc. Securall #4303
7. Goodyear Tire and Rubber Co. Vita Film M-32
8. Linear Films Inc. LFX 8020
9. AEP Industries, Alpha Series Rotary 95032539
10. Bellwether Products Inc. - Product ID HITECH 8020

Date of Last Revision: April 26, 1991

SPECIFICATION FOR FILM, STRETCH WRAP

PROPERTY NUMBERS: 201561 & 201626

General Requirements

The product shall maintain a stretch memory adequate to provide an unionization force during handling and shipment. It shall provide sufficient cling so that heat sealing or other fastening methods is not required for bonding film layers securely. The film shall be suitable for use on a Silver Spiral Wrapper from Radiant Engineering, Inc.

Specific Requirements

Width of Roll

Property No. 201561 20" \pm 0.5" (508 mm \pm 13 mm)

Property No. 201626 60" \pm 0.5" (1524 mm \pm 13 mm)

Length of Roll 5000 - 6000 ft. (1524 - 1829 m)

Thickness of Film 0008" \pm 0.00005" (0.020 \pm 0.001 mm)

Color shall be uniformly transparent

Finishsmooth on both sides

Odor..... free of objectionable odors

Sample Requirement

A one-roll sample of the 20" width is required for testing. Additional rolls may be purchased if necessary.

Packaging

The product shall be single wound on a roll having a core capable of supporting the roll without collapsing or interfering with the easy unrolling of the film.

Qualified Products List

The following products have been tested and comply with the current specifications.

1. Presto Products, Inc. Powergard
2. Borden Chemical Corp. Loadmaster S
3. Englewood Co., Inc. Super Stretch III No. 84-14
4. Ohio Poly Corporation Elastifilm and Phase I
5. Mobil Wrap X-80
6. Co-Ex Plastics, Inc. Securall #4303
7. Goodyear Tire and Rubber Co. Vita Film M-32
8. Linear Films Inc. LFX 8020
10. Bellwether - Hitch 8060 Wrap Stretch Film

Date of Last Revision: April 26, 1994